

iHand55

Professional Field Controller



KEY FEATURES



5.5" sunlight readable display capacitive touch screen for fingers or stylus.



QWERTY full keyboard designed, convenient for different measurement application scenarios.



Quick charge with internal lithium battery to improve efficiency under long time job.



Android 11 operating system equipped to maintain the productivity of numerous survey projects and data.

TECHNICAL SPECIFICATIONS

Hardware Configuration	OS	Android 11
	Processor	CPU: 8 core; 2.0 GHZ
	Storage	3GB RAM+32GB ROM; T-Flash memory card, up to 128GB
	Display	720*1440, 5.5", 500 nit, bright Outdoor Color capacitive multi-touch screen (with touch pen, can be operated with gloves)
	Input Configuration	Qwerty full keyboard, number / letter separate, professional custom smart input method
GNSS Features	GNSS	GNSS antenna, GPS, GLONASS, BDS, AGPS
Communication Interface	Network modem	FDD-LTE B1/B3/B5/B7/B8/B20/B28/B2/B4/B12/B17
		TDD-LTE B38/B39/B40/B41/B34
		TDSCDMA B34/B39
		WCDMA B1/B2/B5/B8/B4
		GSM B2/B3/B5/B8
	Cellular mobile	4G, Dual Nano-SIM
	WiFi	IEEE 802.11 a/b/g/n/ac, Wapi, AP (2.4G / 5G)
Bluetooth	BT5.1, BLE, NFC	
USB	USB Type-C interface, OTG, supports fast charging (5V,3A)	
Power Supply	Battery	9200 mAh internal
	Duration	≥14 hours
	Charging time	4 h (typical)
Application	Camera	Built-in 13 million pixel camera
	Flash	Highlight Flash LED flash (support flashlight function)
	Sensor	Gravity sensor, compass, light sensor, gyroscope
Physical Features	Weight	406g (within battery)
	Size	221 mm*78 mm*16.5 mm
	Operating temperature	-20 C ~ +60 C
	Storage temperature	-30 C ~ +70 C
	Free fall	1.8 m
Shock and vibration	MIL-STD-810H	



AUTHORIZED DISTRIBUTION PARTNER

IP68

23J206

Hi-Target Surveying Instrument Co. Ltd

ADD: Building 13, Tian'An Technology Zone HQ Center, No. 555, North of Panyu RD, Panyu District, 511400 Guangzhou, China.
www.hi-target.com.cn +86-20-28688296 info@hi-target.com.cn